

SCALPING SCREEN RANGE 409

The Maximus 409 has been developed for the smaller end user who require its versatility and ease of transport, without compromising on build quality and reliability. Designed to cope with the heaviest applications, the Maximus 409 can be used in crushing circuits, demolition and construction waste management, aggregates, heavy rock and topsoil applications, as well as many others.

FEATURES & BENEFITS

- Fold over side conveyors suitable for compact areas in waste transfer sites
- High duty, high energy 2 bearing screen box
- Heavy duty Hardox hopper
- Long side conveyors - excellent stockpiling capacity
- Easily transported for hire contractors
- Punch plate, finger decks, bofar decks, mesh all available

TECHNICAL SPECIFICATION

WEIGHT	EST 17,000 Kgs (37,500 Lbs)
TRACKS	400mm
POWER UNIT	Deutz 2.9 Stage V
FEEDER CAPACITY	3.84m ³
FEEDER CONVEYOR	1050mm (42")
COLLECTION CONVEYOR	1050mm
TAIL CONVEYOR	1000mm
MID SIZE CONVEYOR	650mm
FINES CONVEYOR	650mm
TOP & BOTTOM DECK	2.743 x 1.22 (9'x4')
TRANSPORT LENGTH	11345mm (31'-3")
TRANSPORT HEIGHT	3073mm (11'-5")
TRANSPORT WIDTH	2750mm (9'-0")

SCALPING SCREEN RANGE 409

